

# DC Standard Glasswashers

Introducing the new Standard Range Glasswashers from DC, specifically designed to meet the rigorous demands of all UK catering outlets.



## Standard Range

SG35  
SG40  
SG45  
SG50

- **Fast**
- **Economical**
- **Energy Efficient**
- **Space Saving**



### Performance

**Fast two minute wash cycle**  
ensures maximum productivity

**New innovative wash pump**  
increases wash pressure improving results

**Hydrodynamic basket slides**  
ensures optimum wash and rinse coverage

**Rinse thermo-lock**  
delivers perfect rinse temperatures time after time

### Energy and Cost Savings

**Double skinned cabinet door**  
reduces noise and heat emissions whilst lowering running costs

**Reduced water consumption**  
produces the optimum balance between water usage and hygiene

**Improved rinse arms**  
increases initial response by 30% and rotation speed by 20%

### Operation

**Intuitive, simple controls**  
reduces user error and staff training

**EasyClean filters**  
maintenance friendly filters protect critical components

**Chemical auto-dosing**  
eliminates user intervention and prevents over or under dosing

**Auto drain down (optional)**  
ensures rapid drain down with no need for user intervention

**Integral water softener (optional)**  
softens water without the need for an external unit

**'Welcome to a cleaner world'**

## Standard Range Glasswasher Specifications



|                                 | SG35         | SG40         | SG45         | SG50         |
|---------------------------------|--------------|--------------|--------------|--------------|
| <b>Cycle time</b>               | 120 sec      | 120 sec      | 120 sec      | 120 sec      |
| <b>Baskets (x2)</b>             | 350 x 350 mm | 400 x 400 mm | 450 x 450 mm | 500 x 500 mm |
| <b>Height</b>                   | 640 mm       | 690 mm       | 690 mm       | 690 mm       |
| <b>Width</b>                    | 425 mm       | 475 mm       | 525 mm       | 575 mm       |
| <b>Depth</b>                    | 470 mm       | 515 mm       | 545 mm       | 605 mm       |
| <b>Depth with door open</b>     | 705 mm       | 795 mm       | 890 mm       | 950 mm       |
| <b>Usable wash height</b>       | 250 mm       | 300 mm       | 310 mm       | 320 mm       |
| <b>Drain height</b>             | 120 mm       | 120 mm       | 120 mm       | 120 mm       |
| <b>Drain Ø</b>                  | 25 mm        | 25 mm        | 25 mm        | 25 mm        |
| <b>Wash tank</b>                | 11 lts       | 14 lts       | 18 lts       | 20 lts       |
| <b>Boiler</b>                   | 2.8 lts      | 2.8 lts      | 2.8 lts      | 2.8 lts      |
| <b>Water usage</b>              | 2.4 lts p/c  | 2.4 lts p/c  | 2.4 lts p/c  | 2.4 lts p/c  |
| <b>Wash element</b>             | 1.6 kW       | 1.6 kW       | 1.6 kW       | 1.6 kW       |
| <b>Boiler element</b>           | 2.8 kW       | 2.8 kW       | 2.6 kW       | 2.6 kW       |
| <b>Total load</b>               | 3 kW         | 3 kW         | 3 kW         | 3 kW         |
| <b>Amps required*</b>           | 13 Amps      | 13 Amps      | 13 Amps      | 13 Amps      |
| <b>Detergent dosing</b>         | Yes          | Yes          | Yes          | Yes          |
| <b>Rinse aid dosing</b>         | Yes          | Yes          | Yes          | Yes          |
| <b>Water connection</b>         | 3/4 BSP      | 3/4 BSP      | 3/4 BSP      | 3/4 BSP      |
| <b>Required water pressure</b>  | 2-4 bar      | 2-4 bar      | 2-4 bar      | 2-4 bar      |
| <b>Required water flow rate</b> | 10 lts p/min | 10 lts p/min | 10 lts p/min | 10 lts p/min |
| <b>Drain pump</b>               | Optional     | Optional     | Optional     | Optional     |
| <b>Internal softener**</b>      | Optional     | Optional     | Optional     | Optional     |

**Where water hardness exceeds 100ppm a water softener is required.**

\* Can be configured to operate on either 13A or 3Ph+N upon request.

\*\* Internal water softener is not suitable for hot water above 30°C. Softening capacity between regenerations is 125 litres @ 300ppm. Where water hardness exceeds 300ppm and the daily wash cycles exceed 40 per day an alternative softener may be required - please contact your supplier for further information.

**Warranty:** One year parts and labour. Extended warranties available - please ask your supplier.

We reserve the right to change specifications without notice.



**DC Products**

Unit 25 Lodge Hill Industrial Park, Westbury Sub Mendip, Somerset, BA5 1EY

t: +44 (0)1749 870055 f: +44 (0)1749 870056 e: sales@dcproducts.co.uk [www.dcprouducts.co.uk](http://www.dcprouducts.co.uk)

