



**Catalogue**  
FOOD SERVICE  
**Chapter**  
REFRIGERATION

**Specific model**  
UP-251

19089735

24/03/2022

**DENOMINATION:**

Professional refrigerated cabinet with 2 shelves.


**DESCRIPTION :**

- White epoxy coated sheet metal exterior, which provides high resistance to shocks and daily use.
- Inner body in ABS food grade material.
- Rounded edges and corners on the inside for easy cleaning.
- Door with built-in handle.
- Reversible door.
- Fitted with key lock as standard.
- Digital thermometer with temperature control.
- Working voltage: 230 V - 50 Hz.
- Guides inbuilt into the sides of the cabinet with anti-tip system.
- Drain inside the chamber.
- Forced refrigeration. Evaporator integrated into the back wall of the cabinet. A fan distributes the cold, obtaining a uniform temperature inside.
- R-600a hydrocarbon refrigerant gas.
- Operational temperature: -1 °C ÷ +6 °C, Ambient temperature 32 °C.

**POSSIBLE OPTIONS :**

- British plug
- Glass door

**DIMENSIONS**



X Width	626 mm	X Gross width	715 mm
Y Depth	600 mm	Y Gross depth	647 mm
Z Height	850 mm	Z Gross height	975 mm
Net Weight	47,0 kg	Gross Weight	50,0 kg
Net volume	0,319 m3	Gross volume	0,451 m3

**ELECTRICITY TECHNICAL SPECIFICATIONS**

Amperage (A)	0,72A
Electric frequency	50Hz
Electric power	0,091 kW
Voltage	230V - 1N

**GAS TECHNICAL SPECIFICATIONS**

Gas type	R-600a
----------	--------

**COLD TECHNICAL SPECIFICATIONS**

Annual elec. consumption	487,64 kWh
Clasif. Energy efficiency	A
Climate class	4
Cooling gas load	29,000 g
Energy Efficiency Index	23,56 %
Model Type	Counter Cabinet
Power consumption 24h	1,34 kWh
Refrigeration net.vol	112 L
Refrigeration power	0,140 kW

**CONNECTIONS TECHNICAL SPECIFICATIONS**

Single-phase 230V wiring	2X1,5+T - 6 A
--------------------------	---------------

**OTHERS**

Condensation system	Static
---------------------	--------



**Catalogue**  
FOOD SERVICE  
**Chapter**  
REFRIGERATION

**Specific model**  
UP-251

19089735

24/03/2022

