



Catalogue
FOOD SERVICE
Chapter
REFRIGERATION

Specific model
UP-251 GD

19089741

24/03/2022

DENOMINATION:

Professional display refrigerated cabinet with 2 shelves.

DESCRIPTION :

Professional refrigerated display cabinets:

- White epoxy coated sheet metal exterior, providing high resistance to impact and daily use.
- Inner body in ABS food grade material.
- Equipped with fluorescent interior lighting, which helps to attract and display the products.
- Double glass door with handle incorporated in the frame.
- Reversible door with aluminium frame, which gives it an elegant and very aesthetic finish.
- Door with built-in handle.
- Fitted with key lock as standard.
- Digital thermometer with temperature control.
- Working voltage: 230 V - 50 Hz.
- Guides integrated in the cabinet walls with anti-tilt system.
- Plastic-coated rod grids, easily removable for cleaning.
- Rounded edges and corners on the inside for easy cleaning.
- Drainage inside the chamber.
- Forced cooling. Evaporator integrated in the rear wall of the cabinet, and a fan distributes the cold, obtaining a homogeneous temperature inside.
- Hydrocarbon refrigerant gas R-600a.
- Working temperature: -1 °C ÷ +6 °C, ambient temperature 32 °C.


POSSIBLE OPTIONS :

- British plug

STANDARD OPTIONS :

- Glass door

DIMENSIONS



X Width	626 mm	X Gross width	715 mm
Y Depth	600 mm	Y Gross depth	647 mm
Z Height	850 mm	Z Gross height	975 mm
Net Weight	53,0 kg	Gross Weight	55,0 kg
Net volume	0,391 m3	Gross volume	0,451 m3

ELECTRICITY TECHNICAL SPECIFICATIONS

Amperage (A)	0,72A
Electric frequency	50Hz
Electric power	0,091 kW
Voltage	230V - 1N

GAS TECHNICAL SPECIFICATIONS

Gas type	R-600a
----------	--------

COLD TECHNICAL SPECIFICATIONS

Climate class	4
Cooling gas load	29,000 g
Refrigeration power	0,140 kW

CONNECTIONS TECHNICAL SPECIFICATIONS

Single-phase 230V wiring	2X1,5+T - 6 A
--------------------------	---------------

OTHERS

Condensation system	Static
---------------------	--------



Catalogue
FOOD SERVICE
Chapter
REFRIGERATION

Specific model
UP-251 GD

19089741

24/03/2022

