



Catalogue
FOOD SERVICE
Chapter
REFRIGERATION

Specific model
UP-251 SS

19089729

24/03/2022

DENOMINATION:

Professional refrigerated cabinet (stainless steel exterior) with 2 shelves.


DESCRIPTION :

- Exterior made of stainless steel.
- Inner body made of ABS food grade material.
- Rounded edges and corners on the inside for easy cleaning.
- Door with built-in handle.
- Reversible door.
- Fitted with key lock as standard.
- Digital thermometer with temperature control.
- Working voltage: 230 V - 50 Hz.
- Guides inbuilt into the sides of the cabinet with anti-tip system.
- Drain inside the chamber.
- Forced refrigeration. Evaporator integrated into the back wall of the cabinet. A fan distributes the cold, obtaining a uniform temperature inside.
- R-600a hydrocarbon refrigerant gas.
- Operational temperature: -1 °C ÷ +6 °C, Ambient temperature 32 °C.

POSSIBLE OPTIONS :

- British plug
- Glass door

DIMENSIONS



X Width	626 mm	X Gross width	715 mm
Y Depth	600 mm	Y Gross depth	647 mm
Z Height	850 mm	Z Gross height	975 mm
Net Weight	49,0 kg	Gross Weight	52,0 kg
Net volume	0,319 m3	Gross volume	0,451 m3

ELECTRICITY TECHNICAL SPECIFICATIONS

Amperage (A)	0,72A
Electric frequency	50Hz
Electric power	0,091 kW
Voltage	230V - 1N

GAS TECHNICAL SPECIFICATIONS

Gas type	R-600a
----------	--------

COLD TECHNICAL SPECIFICATIONS

Annual elec. consumption	487,64 kWh
Clasif. Energy efficiency	A
Climate class	4
Cooling gas load	29,000 g
Energy Efficiency Index	23,56 %
Model Type	Counter Cabinet
Power consumption 24h	1,34 kWh
Refrigeration net.vol	112 L
Refrigeration power	0,140 kW

CONNECTIONS TECHNICAL SPECIFICATIONS

Single-phase 230V wiring	2X1,5+T - 6 A
--------------------------	---------------

OTHERS

Condensation system	Static
---------------------	--------





Catalogue
FOOD SERVICE
Chapter
REFRIGERATION

Specific model
UP-251 SS

19089729

24/03/2022

