



SILVERLINK 600

Whether you're cooking eggs, bacon, burgers or vegetables, the versatile Silverlink 600 Electric Griddle won't let you down. The griddle has a chrome surface which both heats up quicker, and transfers heat to food more efficiently than standard griddles, with less energy loss as well as reduced energy radiation, which keeps the kitchen cooler for staff and reduces pressure on the ventilation system. What's more, the griddle features two separately controlled heat zones, which give you the option of operating either zone independently to provide a smaller cooking area during quiet periods as well as offering versatility when cooking two separate meals simultaneously. It's perfect for cafes, pubs and restaurants.

PRODUCT OPTIONS AND ACCESSORIES

- SB7 750 GRIDDLE SPLASHB
- CC7 Lincat Silverlink 600 Free-standing Ambient Open-Top Pedestal with Doors - W 750 mm
- CN7 Lincat Silverlink 600 Free-standing Ambient Open-Top Pedestal without Doors - W 750 mm
- SLS7 Lincat Silverlink 600 Free-standing Floor Stand - for units W 750 mm
- HC7 Lincat Silverlink 600 Free-standing Heated Open-Top Pedestal with Doors - W 750 mm - 0.5 kW
- HCL7 Lincat Silverlink 600 Free-standing Heated Pedestal with Legs and Doors - W 750 mm - 0.75 kW

PRODUCT FEATURES

- Two separately controlled heat zones give you the option of operating either zone independently to provide a smaller cooking area during quiet periods as well as offering versatility when cooking two separate meals simultaneously
- Chrome surface heats up quicker than standard griddles with less energy loss as well as reduced energy radiation, keeping the kitchen cooler for staff and reducing pressure on the ventilation system
- Transfers heat to food more efficiently than a standard griddle
- Thermostatically controlled to give accurate temperatures during the cooking process for consistent results
- Removable front drainer drawer which also makes for easy cleaning. Ideal for busy establishments
- The plate is fully welded into the frame to prevent leaks and places where food and carbon can build up

WEIGHTS & DIMENSIONS

Width	750 mil
Depth	620 mil
Height	330 mil
Weight	48 kg

SHIPPING DETAILS

Ship Width	85.5 cm
Ship Depth	70 cm
Ship Height	63.5 cm
Ship Weight	52.8 kg
Ship Method	Small Parcel (FedEx, UPS, DHL)
Shipping Package Type	Pieces
Shipping Origin Zip Code	LN6 3QZ, UNITED KINGDOM
Quick Ship Product	No

PRODUCT CERTIFICATIONS



ENERGY SPECS

Primary Energy Type	Electric	Electrical Kilowatts	6 kW
Electrical Amps Per Conductor	Single Phase 26.1/Three Phase L1=13.0; L2=13.0; L3=N/	Electrical Plug Type	Hardwired
Electrical Total Amperage	26.1 A	Number of Electrical Plugs	Not Applicable
Electrical Volts	230-400V	Number of Electrical Conductor Wires	1
Electrical Total Wattage	6000 W	Dedicated Circuit Required	Yes
		Electrical Remarks	Single, Three

ADDITIONAL SPECIFICATIONS

Construction Materials	Stainless Steel	Number of Heating Zones	2
Control Type	Rotary Control Knob	Plate Thickness	12 mm
Cooking Area Plate Depth	405 mm	Plate Shape	Rectangle
Cooking Area Plate Width	712 mm	Ventless Cooking Technology	No
Cooking Plate Finish Material Type	Chrome Plated	Temperature Maximum	250 °C
Lower Platen Surface Type	Smooth	Temperature Minimum	50 °C
Number Of Controls	2	Thermostat Element Location	Under Plate Mount

BIDDING SPECIFICATIONS (SHORT FORM SPECS)

Bidding Specifications Not Available.

TECHNICAL DRAWING

