

### LINCAT OPUS DUAL FUEL [PROPANE GAS] FREE-STANDING OVEN RANGE - 6 BURNERS - W 900 MM - 40.2 KW

MODEL: OD8007/P



The first thing that strikes you about this Opus 800 dual fuel oven is its power. It benefits from the best of both the focused, instant heat from the mighty dual concentric gas burners, and the even cooking of the electric oven. Built to withstand the rigours of even the busiest kitchen, the large 6 x GN1/1 capacity oven is up to the task of delivering high volumes of top quality food, and even enables six different foods to be cooked simultaneously. So whether you're cooking in a restaurant, a large pub, or a school canteen, the dual fuel oven has you covered. Strong and sturdy and built to last, the oven also comes with individual heavy-duty single cast iron supports.

### PRODUCT OPTIONS AND ACCESSORIES

LK06 OPUS 800 LEG KIT

#### **PRODUCT FEATURES**

- Powerful 7.5kW dual concentric Burners for focused heat distribution from a fast boil to a low simmer
- Individual heavy-duty single cast iron supports, built to withstand the rigours of the busiest kitchen
- Low flue to allow use of the complete hob top
- Powerful 6kW twin fan assisted oven for even cooking results
- Large 6 x GN1/1 capacity oven enabling six different foods to be cooked simultaneously







# LINCAT OPUS DUAL FUEL [PROPANE GAS] FREE-STANDING OVEN RANGE - 6 BURNERS - W 900 MM - 40.2 KW

MODEL: OD8007/P

WEIGHTS & DIMENSIONS	
Width	900 mil
Depth	800 mil
Height	912 mil
Weight	186 kg

SHIPPING DETAILS	
Ship Width	100 cm
Ship Depth	85 cm
Ship Height	107 cm
Ship Weight	204.6 kg
Number of Shipment Parcels	1
Shipping Origin Zip Code	LN6 3QZ, UNITED KINGDOM
Quick Ship Product	No
Returnable Item	No

#### **PRODUCT CERTIFICATIONS**



ENERGY SPECS	
Primary Energy Source Type	Electricity, Gas
Electrical Amps	Single Phase 26/Three Phase L1=9.0; L2=8.7; L3=8.7
Electrical Voltage	230 volts/400 volts
Electrical Watts	6060
Electrical Phase	Single, Three
Kilowatts	40.2 kW
Number of Electrical Conductor Wires	1
Electrical Connection Type	Direct Hardwired
Electrical Plug Type	Hardwired

Number of Electrical Plugs	Not Applicable
Dedicated Circuit Required	Yes
Gas Type	Propane
Gas Inlet Size	0.75 in
Gas Inlet Pressure Required	37 mBar
Gas Total BTUs	137168 BTU
Gas Consumption at Max Use Per Hour	2.87 m <sup>3</sup>
Total Heat Input at Max Use	40.2 kW, 137162 BTU per hour
Energy Saving	No

Lincat reserves the right to modify specifications or discontinue models without incurring obligation. Dimensions nominal.

Document Auto-Generated January 23, 2024





# LINCAT OPUS DUAL FUEL [PROPANE GAS] FREE-STANDING OVEN RANGE - 6 BURNERS - W 900 MM - 40.2 KW

MODEL: OD8007/P

ADDITIONAL SPECIFICATIONS			
Control Type	Mechanical	Open or Sealed Burners	Sealed
Cooking Plate Finish Material Type	Stainless Steel	Oven Power Rating	6 kW
Exterior Finish Color	Stainless Steel	Oven Temperature Maximum	250 °C
Exterior Trim Finish Color	Stainless Steel	Oven Temperature Minimum	120 °C
Gastronorm Capacity	6 x GN1/1	Restaurant or Heavy Duty	Yes
High Altitude Kit Available	No	Shelf Depth	530 mm
Number of Heating Zones	6	Shelf Width	770 mm
Number of Hot Top Burners	6	Watts Per Element	7000
Number of Shelf Positions	5	Cooking Equipment	Sealed Burner
Number of Shelves	3	BTUs Per Burner	7 KW

SELECT COOKING EQUIPMENT	NUMBER OF		POWER RATING	ARRANGE- MENT	WIDTH	DEPTH
Sealed Burner 1		6			300 mm	300 mm
SELECT BASE EQUIPMENT	NUMBER OF		CUBIC CAPACITY EACH	WIDTH	DEPTH	HEIGHT
Standard Oven 1		1		825 mm	530 mm	410 mm

#### **BIDDING SPECIFICATIONS**

Bidding Specifications Not Available.

Document Auto-Generated January 23, 2024




without incurring obligation. Dimensions nominal.


Lincat reserves the right to modify specifications or discontinue models




MODEL: OD8007/P

#### **TECHNICAL DRAWING**







Lincat reserves the right to modify specifications or discontinue models without incurring obligation. Dimensions nominal.

Document Auto-Generated January 23, 2024

