



Model SG18 Tube Fired Gas Fryer



Project _____

Item number _____

Quantity _____

Model SG18

STANDARD SPECIFICATIONS

CONSTRUCTION

- Welded tank with an extra smooth peened finish ensures easy cleaning.
- Long-lasting, high-temperature alloy stainless steel heat baffles are mounted in the heat exchanger tubes to provide maximum heating and combustion efficiency.
- Standing pilot light design provides a ready flame when heat is required.
- Stainless steel front, door, side, and splashback.
- Heavy duty 3/16" (.48 cm) door hinge.

CONTROLS

- Millivolt thermostat maintains selected temperature automatically between 200°F (93°C) and 400°F (190°C-CE).
 - Integrated gas control valve acts as a manual and pilot valve, automatic pilot valve, gas filter, pressure regulator, and automatic main valve.
 - Gas control valve prevents gas flow to the main burner until pilot is established and shuts off all gas flow automatically if the pilot flame goes out.
 - Temperature limit switch safely shuts off all gas flow if the fryer temperature exceeds the upper limit.
 - New Solstice burner/baffle design.***
 - Increases cooking production.
 - Lowers flue temperature.
 - Improves working environment.
 - Generates more production per BTU.
- ***Compared to previous models.

OPERATIONS

- Front 1 1/4" (3.2 cm) full port drain for quick draining.
- 9" (22.9 cm) clearance allows for ease of cleaning.
- Reversible tube rack converts fry depth from basket operation to free floating products.

APPROVALS

- CSA Certified (AGA, CGA)
- NSF Listed
- MEA Approved
- CE Certified
- Australian Gas Assoc. Certified (AuGA)



Patent Pending

Financing Available-Maytag Commercial Lease Program
Call 1-800-666-6812 for Details

STANDARD ACCESSORIES

- Choice of basket options
 - ☐ Two nickel-plated, oblong, wire mesh baskets
 - ☐ One nickel-plated, square, wire mesh basket
- One nickel-plated tube rack
- One drain extension
- One drain line clean-out rod
- Fryer cleaner sample
- Rear gas connection
- Manual gas shutoff
- 1 1/4" (3.2 cm) full port drain valve
- Built-in integrated flue deflector
- Removable basket hanger for easy cleaning
- 9" (22.9 cm) adjustable legs
- Cabinet - stainless steel front, door, and sides
- Tank - mild steel

AVAILABLE OPTIONS & ACCESSORIES

- ☐ Stainless steel tank
- ☐ Stainless steel back
- ☐ 9" (22.9 cm) adjustable casters
- ☐ Triple baskets
- ☐ Covers



Technical drawing of the front view of the refrigerator. The drawing shows the refrigerator with its door open. Dimensions are indicated in inches and centimeters in brackets. The height of the refrigerator is 18 [45.7] inches. The width of the refrigerator is 52 5/16 [132.9] inches. The width of the door is 18 [45.7] inches. The drawing also shows a curved dashed line indicating the door's swing and a small detail of the door's interior.

Technical drawing of the 200 Series Gas Range, showing front, side, and rear views with dimensions in inches and millimeters.

Front View Dimensions:

- Top width: 19 5/8 [49.8]
- Top panel width: 8
- Control panel width: 8
- Base width: 16 1/16 [40.8]
- Base offset: 1 25/32 [4.5]

Side View Dimensions:

- Top width: 34 [86.4]
- Top panel depth: 5/8 [1.6]
- Control panel depth: 34 [86.4] NOM.
- Base depth: 15 7/32 [38.6]
- Base offset: 11 25/32 [29.9]
- Base offset: 9 [22.9] NOM.
- Base offset: 24 3/4 [62.9]
- Base offset: 1 9/16 [4.0]
- Base offset: 4 23/32 [12.0]

Rear View Dimensions:

- Top width: 34 [86.4]
- Top panel depth: 11/16 [1.8]
- Control panel depth: 46 1/8 [117.2]
- Base depth: 15 1/16 [38.2]
- Base offset: 9 13/16 [24.9]

Labels:

- 1-1/4 INCH (3.2 CM) NPT FULL PORT DRAIN VALVE
- INTEGRAL FLUE DEFLECTOR
- GAS CONNECTION 3/4 INCH NPT. CE AND AuGA MODELS USE 3/4 INCH BSP ADAPTER ADDING 1-1/2 INCH (3.8 CM) TO THE CONNECTION.

Gas Input Per Hour			
140,000 BTUs / 40 kW (CE) / 145 megajoules (AuGA)			
Gas Type*	Recommended Minimum Store Manifold Pressure	Burner Manifold Pressure	*For other gas types, contact your Dealer/Distributor.
Natural Gas	7" W.C. / 17.4 mbars / 1.75 kPa	4" W.C. /10 mbars / 1 kPa	Check plumbing/gas codes for proper gas supply line sizing.
L.P. Gas	13" W.C. / 32.4 mbars / 3.25 kPa	10" W.C. / 25 mbars / 2.5 kPa	
Clearance Information	Fryer Front	Fryer Sides, Rear, Bottom to any combustible material	Fryer Flue Area
All Models	30" (76.2 cm) min.	6" (15.2 cm) Do not Curb Mount	Do not block or restrict the flue gasses from flowing into the ventilation system.
ELECTRICAL		OIL CAPACITY	
Control Type	Voltage / Phase / Frequency	Amps	70 - 90 pounds (32 - 41 kg)
Millivolt	Not required	0	
SHIPPING INFORMATION		PERFORMANCE CHARACTERISTICS	
Shipping Weight	Shipping Cube	Shipping H x W x L	Cooks 120 lbs (54 kg) of fries per hour Frying area 18 x 18 x 4 ~ 4 ¾ in 47.7 x 45.7 x 10.2 ~ 12.1 cm
216 lbs 98 kg	23 ft³ .65 m³	45 ¼ x 22 ¾ x 38 ½ in 114.9 x 57.8 x 97.8 cm	
SHORT FORM SPECIFICATION			
Provide Pitco Model SG18 tube fired gas fryer. Fryer shall have an atmospheric burner system combined with five stainless steel heat tubes utilizing high temperature alloy stainless steel baffles. Fryer shall have a deep cool zone; minimum 16% of total oil capacity to trap burnt particles, crumbs and black specks. Fryer cooking area shall be 18"x 18" (45.7 cm x 45.7 cm) with a cooking depth between 4" (10.2 cm) and 4 ¾"(12.1 cm). Heat transfer area shall be a minimum of 948 sq. inches (6,116 sq. cm). Provide accessories as follows.			
TYPICAL APPLICATION			
Frying a wide variety of foods in a limited amount of space. Frying that requires a high volume production rate.			

