



C501 – Undercounter Glass/dishwasher

- 2 Year warranty
- Partial double skin reducing heat loss
- Supplied with two open racks
- Accurate detergent and rinse aid dosed by reliable peristaltic pumps as standard
- Drain pump optional
- Scrap trays as standard
- Operational self-diagnostics
- Three standard cycle options with further options available
- Cycle times can be tailored to site requirements
- Selectable energy saving mode
- Automatic self-cleaning at end of service
- Selectable thermostop ensures optimum rinse temperatures
- Operational self-diagnostics
- Bright LED display with soft touch controls
- Twin traffic light display indicates machine status



C501 – Undercounter Glass/dishwasher

	C501
Width	580mm
Depth	610mm
Height	815mm+Feet
Feet height	10mm-20mm
Basket size	500 x 500mm
Maximum useable height	320mm
Door opening	365mm
Number of standard cycles	3
Standard cycle times	70/120/150 Seconds - adjustable
Special cycles	Long cycle = 6 minutes
Self-cleaning program	Yes
Water consumption per cycle	2.7 Litres
Wash tank capacity	20 Litres
Power – Single phase options	2.6kW (13AMP) / 4.5kW (20AMP) / 6.5kW (30AMP)
Power – Three phase	6.5kW (16AMP)
Boiler element	6kW (2/4/6)
Washtank element	2.1kW
Detergent pump	Peristaltic – precise delivery
Rinse aid pump	Peristaltic – precise delivery
Drain type	Manual drain plug
Drain pump	Optional
Water supply pressure	2 to 4 Bar
Water supply temperature	10 to 50 Degrees Celsius
Body construction	Partial double skin
Door/hood construction	Double Skin
Tank construction	Fabricated
Scrap trays	Yes
Wash pump type	Dual flow
Wash pump power	470W
Wash arm - upper	Composite parallel arms
Wash arm - lower	Composite parallel arms
Rinse arm - upper	Combined with wash arms
Rinse arm - lower	Combined with wash arms
Open basket	2
User Interface (Controls)	Soft touch controls